DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011

75x39-K-2.0

1. LEK no. KE 0018 2. Model Insert

3. Intended use Insert for solid fuels without heating water

3

4. Manufacturer Austroflamm GmbH Austroflamm-Platz 1

A-4631 Krenglbach

5. Representative

6. System for verifying constancy of per-

formance

| | 75x39-K-2.0 |
|---|-----------------------------------|
| Notified Body/ name of test laboratory | SZU |
| Test laboratory identification number/test report number | 1015 / 1015- CPR-30-16564/1/TZ |
| Harmonized technical specification | EN 16510-2-2:2022 |
| Fire safety | fulfilled |
| Reaction to fire | A1 as per EN 13501-1 |
| dR Distance rear [mm] | 0 |
| dS1 Distance left [mm] | 0 |
| dS2 Distance right [mm] | 0 |
| dC Distance above [mm] | 750 |
| dP Radiation front [mm] | 1500 |
| dB Distance bottom [mm] | - |
| Fire hazard through burning firewood falling out of the stove | fulfilled |
| Cleanability | fulfilled |
| Emission of combustion products | fulfilled |
| Emission (CO) of combustion products at nominal heat output [%] | ≤ 0.10 |
| Emission (CO) of combustion products at reduced heat output [%] | NPD |
| Flue gas temperature in the measuring section at nominal heat output [°C] | 260 |
| Flue gas temperature at the nozzle at nominal heat output [°C] | 312 |
| Surface temperature | fulfilled |
| Electrical safety | NPD |
| Release of hazardous substances | NPD |
| Maximum operating pressure [bar] | - |
| Maximum operating pressure option | not relevant |
| Mechanical strength (for supporting a chimney) | NPD |
| Heat output / energy efficiency | fulfilled |



DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011



75x39-K-2.0

 1. LEK no.
 KE 0018

 2. Model
 Insert

3. Intended use Insert for solid fuels without heating water

4. Manufacturer

Austroflamm GmbH

Austroflamm-Platz 1

A-4631 Krenglbach

5. Representative6. System for verifying constancy of per-

formance

| | 75x39-K-2.0 |
|---|-------------|
| Nominal heat efficiency [kW] | 10.0 |
| Nominal room heat output [kW] | 10.0 |
| Nominal water heat output [kW] | - |
| Efficiency / thermal efficiency / fuel energy efficiency at nominal heat efficiency [%] | 78 |

The performance of the product under numbers 1 and 2 corresponds to the declared performance. The manufacturer alone is responsible for the production of this declaration of performance under number 4. Signed for the manufacturer and on behalf of the manufacturer by:

Krenglbach, 05/02/2025

Doris Pfeiffer Managing Director